

# RIBBON SNOWBLOWER SPECS



| FEATURES  | STANDARD | OPTIONAL |
|---|----------|----------|
| Raising/lowering, chute rotation and chute deflector hydraulically controlled | ✓        |          |
| Mechanically driven with shear pin protection                                 | ✓        |          |
| End plates 3/8" thick steel   | ✓        |          |
| Two-stage centre gear-drive, serrated ribbon augers                           | ✓        |          |
| Blower height 38"   | ✓        |          |
| Impeller 7.5" x 24" diameter, with 5 scoop-type blades                        | ✓        |          |
| 2 piece replaceable impeller housing liner                                    | ✓        |          |
| Chute rotation, 15" diameter ball bearing system                              | ✓        |          |
| Two 1.5" thick hardened skid shoes  | ✓        |          |
| 1/2" x 6" thick hardened skid shoes   | ✓        |          |
| Sidewalk chute  | ✓        |          |
| Trackless yellow finish   | ✓        |          |
| Fixed truck loading chute   |          | ✓        |
| Hydraulic telescopic truck loading chute (MT6 & MT7 only)                     |          | ✓        |

| MODEL                 | LENGTH*       | WIDTH*        | HEIGHT*       | WEIGHT*           |
|-----------------------|---------------|---------------|---------------|-------------------|
| 51" Ribbon Snowblower | 56" (1422 mm) | 51" (1295 mm) | 91" (2311 mm) | 1527 lbs (541 kg) |
| 60" Ribbon Snowblower | 56" (1422 mm) | 60" (1524 mm) | 91" (2311 mm) | 1640 lbs (582 kg) |

**FOR MORE INFORMATION PLEASE VISIT [TRACKLESSVEHICLES.COM](http://TRACKLESSVEHICLES.COM)**

\*All measurements provided are approximate and based on shipping dimensions.